

# TYPE APPROVAL CERTIFICATE

Certificate No. : HMB32779-AE003 Initial Approval : 7th July, 2014

**Product** : Pressure Switch **Manufacturer** : Trafag spol.s r.o.

Vilemovska 2129 34701 Tachov, Czech Republic

**Product Description :** Type : Picostat 9K4, 9M4

(Picostat PST4K, PST4M with micro switch 42 and 84)

" See Appendix 1 "

Approval Condition: "See Appendix 1"

**THIS IS TO CERTIFY** that the above-mentioned product has been approved in accordance with the relevant requirement of this Society's Rules and / or of the recognized standards as follows and entered in the "List of Approved Manufacturers and Type Approved Equipment".

Pt. 6, Ch. 2, Art. 301 of the Rules for Classification, Steel Ships.

This Certificate is valid until 6th July, 2024 Issued at Busan, Korea on 24th September, 2019



This certificate is signed electronically in accordance with IMO FAL.5/Circ.39/Rev.2. Validation and authentication of the certificate can be confirmed from "http://e-cert.krs.co.kr" by using the tracking No (ME19026862207) and certificate No.(HMB32779 -AE003).



KOREAN REGISTER OF SHIPPING

General Manager of Marine & Ocean Equipment Team

Note: 1. This certificate will be valid subject to complying with the approval conditions described on the certificate and/or on the Rules of this Society.

- $2. \ This \ certificate \ will be invalid from \ the \ expiry \ date \ a forementioned \ unless \ the \ extension \ or \ renewal \ has been \ granted \ to \ the \ applicant \ or \ the \ manufacturer.$
- 3. Any significant modifications or changes in design or construction to the above product without approval from this Society will render this certificate invalid.
- 4. Should the specified rules, regulations or standards be amended during the validity of this certificate, the product is to be re-approved by this Society in accordance with the requirements as amended.

Form AC-2A (2019.01) 1/2

# Appendix 1

# **Product Description and/or Approval Condition**

Certificate No: HMB32779-AE003 Date of Issue: 24th September, 2019

# A. Product Description

```
1. Product Specification
  1) Product Description
       Sensor type: Piston, Membrane
     - Output : Floating change-over contact
     - Switching differential: not adjustable
     - Enclosure: IP65
      - Micro switches type : 42 (Standard, Silver contacts), 84 (Gold plated contacts)
 2) Type designation
       9K4. a, b, c, d
       a = Microswitch : 42,48
       b = Range : 78, 79, 80, 81, 82, 83, 84, 85, 86 (1~10 to 40~400bar) c = Sensor : 756 (Range 78, 79), 757 (Range 80, 81) 758 (Range 82, 83), 759 (Range 84, 85, 86)
       d = Pressure connection : 02, 03, 04
     - 9M4. a, b, c, d
       a = Microswitch : 42 ,48
       b = Range : 78, 79, 80, 81, 82, 83 (1~10 to 10~100bar)
       c = Sensor : 761 (Range 78, 79), 762 (Range 80, 81)
763 (Range 82, 83)
```

# 2. Approved Drawings and Documents

```
1) Drawings

- Dwg. No. C22667h, C22668i

2) Data sheet

- H72368h (2018.12), H72369h (2018.12)
```

d = Pressure connection : 02, 03, 04

#### 3. Test Reports, etc.

1) Environmental Test Report
- Test Report No. V-12072 on 21th May 2013
- Test Report No. V-13075 on 19th September 2013
- Test Report No. V-13092 on 10th January 2014

#### **B.** Approval Condition

#### 1. Application & Limitation

1) This approval is granted on the basis of the test reports and the approved documentation.

### 2. Individual Product Cert. and Drawing Approval Requirement

1) Individual Product Certification is not required.

#### 3. Marking

1) The product or packing is to be marked with the manufacturer's name and type designation on a suitable position.

#### 4. Others

1) Test condition

Test	Condition	Remark
EMC	Not Applied	*1
Temperature	0 ~ +80℃	<del>_</del>
Vibration	Acceleration ±4g	
Degree of protection	IP65	

<sup>\*1:</sup> Non-power equipment

< End of Certificate >

Form AC-2A (2019.01) 2/2